




NVH220 Lophius AI Bluetooth

Industrial Handheld Scanners

					
1.8m drop	1D & 2D	Acuscan	Advanced Scripting	AI-Powered Barcode Detection	Bluetooth 5.0
					
DPM	EasySet	Ethernet	IP64	Laser aimer	Micro USB
					
RS232	Warranty 3 Years	White Illumination			



Features

AI-Powered Scanning Technology.

The NVH220 Lophius AI BT is equipped with Newland's UIMG and AI-Powered Barcode Detection scanning technologies. These advanced systems enable rapid, accurate, and reliable decoding of both 1D and 2D barcodes, even when they are damaged or distorted, as well as on reflective and curved surfaces. AI-powered devices utilize computer vision and self learning to interpret barcodes accurately. They efficiently analyze images to detect, locate, and read barcodes. The NVH220 Lophius AI BT excels in challenging conditions, demonstrating advanced decoding performance and providing a reliable scanning solution that functions flawlessly in any situation.

High-Performance DPM Scanning

The NVH220 Lophius AI BT is distinguished by its outstanding ability to decode DPM barcodes, including those created using laser part marking and dotting techniques. Equipped with an upgraded dual-core processing platform, the NVH220 offers enhanced performance while consuming less power. This results in faster and more stable decoding, as well as improved image capture.

Robust by Design.

The NVH220 Lophius AI BT is built for durability, featuring a robust design that can endure challenging conditions. Its high-protection construction and IP64-sealed housing ensure reliable performance, even in environments with dust and water exposure, as well as after repeated drops from heights of up to 1.8 meters.

Advanced Illumination.

The NVH220 Lophius AI BT features both red and blue direct illumination and white diffuse lighting. These lighting options can be easily activated using the auto-learning function button located on the top of the device. With this feature, the NVH220 automatically adjusts brightness and light source to optimize barcode decoding, even on challenging materials. This includes reflective surfaces, curved shapes, varied backgrounds (ranging from low to high contrast), and different barcode colors.

Reliable Data Transmission.

The NVH220 Lophius AI BT, equipped with Bluetooth 5.0, ensures fast wireless communication with low latency. This stable and reliable connection supports data transmission over a range of up to 150 meters, providing all-day flexibility and efficiency on the work floor.

NVH220 Lophius AI Bluetooth

Data Capture

1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code128, Code93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, Code 39, AIM 128, GS1 Composite, GS1-128(UCC/EAN), ISBT 128, Code 11, MSI-Plessey, Plessey, etc.
2D	QR Code, PDF417, Micro QR, Data Matrix, AZTEC.
Aiming	Cross laser (650nm)
Depth of Field Code 39 (20mil)	65 mm - 350 mm
Depth of Field Code 39 (5mil)	0 mm - 160 mm
Depth of Field EAN 13 (13mil)	15 mm - 220 mm
Depth of Field QR (10mil)	0 mm - 160 mm
Depth of Field QR (20mil)	0 mm - 225 mm
Field of View Horizontal	33°
Field of View Vertical	22°
Illumination	Direct: red & blue LEDs, Diffuse: white LED
Image Sensor	1280 x 800 CMOS
Minimal Print Contrast	15%
OCR	Optional
Resolution	≥1.25mil (1D), ≥2.82mil (2D)
Scan Angle Pitch	±50°
Scan Angle Roll	360°
Scan Angle Skew	±50°

Physical

Battery Type	2,900 mAh
Current @ 3.8VDC Operating	370 mA (red LED by default)
Current @ 3.8VDC Standby	90 mA
Dimensions	Scanner: 68(W) × 86(D) × 180(H) mm, Cradle: 103(W) x 127(D) x 123(H) mm
Expected Battery Life	≥17 hours of continuous operation, up to 60,000 scans per charge
Expected Charge Time	3 hours
Interfaces	RS-232, Ethernet, TCP/IP, ModbusTCP, Profinet, MELSEC/SLMP
Notifications	Beep, LED, Vibration
Power Consumption	1400 mW (typical)
Weight	Scanner: 218g (with battery); Cradle:217g

Wireless

Radio Technology	Bluetooth 5.0
Wireless Distance (max.)	150m (line of sight)

Environmental

Charge Temperature	0°C to 45°C (32°F to 113°F)
Drop	1.8 m
Electro Static Discharge (ESD)	±8 kV (direct discharge), ±16 kV (air discharge)
Humidity	5% to 95% (non-condensing)
IP Rating	IP64
IP Rating with Cradle	IP42
Operating Temperature	-20°C to 50°C (-4°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)

Software

Configuration Tools	EasySet
---------------------	---------

Certifications

Certifications Hardware	FCC, RoHS 2.0, IEC 60825, IEC 62471, CCC, CE, ISO16750
-------------------------	--

Warranty

Comprehensive Service Contract	3 Years, 5 Years
Warranty Extension	+2 Years
Warranty Standard	3 Years

Accessories

Accessories Optional	USB cable, Multiplug adapter, RS-232 cable, Wall mount clip, Ethernet cable, Rubber boot
Accessories Standard	USB cable, Power adapter, Stand/Docking station

What's in the box?

NLS-NVH220B-V2-XD	NVH220 Lophius AI BT, Docking station, USB cable, 5V power supply
-------------------	---

Accessories

Charging/Power

ADP220 Power Supply for NVH220 Lophius Series (ADP220)

Cables

CBL-0275E Ethernet cable for NVH220 AI series (CBL-0275E)
CBL017U RJ to USB-C Cable for HR, FR and FM Series (CBL017U)
CBL030UA USB Cable for HR12, HR32 and HR52 Series (CBL030UA)
CBL036UA USB Cable for HR, FM, and FR Series (CBL036UA)
CBL037R RS232 Cable for HR, FR, and FM Series (CBL037R)
CBL042UA USB Cable for HR, FM, and FR Series (CBL042UA)
CBL048U USB Cable for Ingenico iCT220 (CBL048U)
CBL105U USB White Cable for HR Series (CBL105U)
CBL128R Cable for Magellan Connection (CBL128R)

Peripherals

EX232 Remora (NLS-EX232-01)

Base Stations

NLS-STD-WM001 Wall Mount Clip for HR Series (NLS-STD-WM001)



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved