
Getac



ZX10 FULLY RUGGED TABLET

- Qualcomm[®] Snapdragon™ 660, Octa-core Processor
- 10.1" LumiBond[®] display with Getac sunlight readable technology and glove-enabled capacitive touchscreen
- Dual hot-swappable batteries for uninterrupted operation
- 6ft drop, MIL-STD-810H and IP66 certified
- Optional 1D/2D imager barcode reader





SPECIFICATIONS

Operating System	Android™ 11.0
Mobile Computing Platform	Qualcomm [®] Snapdragon™ 660, Octa-core 1.95GHz Max. 2.2GHz
VGA Controller	Qualcomm [®] Adreno™ 512 GPU
Display	10.1" TFT LCD WUXGA (1920 x 1200) Protection film 800 nits LumiBond [®] display with Getac sunlight readable technology Capacitive multi-touch screen
Storage & Memory	4GB LPDDR4, 64GB eMMC Optional: 6GB LPDDR4, 128GB eMMC
Device Button	Power button 4 tablet programmable buttons
Pointing Device	Touchscreen - Capacitive multi-touch screen - Optional: Dual mode touchscreen (multi-touch)
Expansion Slot	Optional: 1D/2D imager barcode reader Optional: Smart card reader Optional: HF RFID/NFC combo reader ⁱ
I/O Interface	8M pixels webcam x 1 16M pixels auto focus rear camera x 1 Audio in/out combo x 1 DC in Jack x 1 USB 3.2 Gen 1 Type-C w/ DP & PD x 1 USB 2.0 (Host) x 1 MicroSD x 1 Docking connector x 1 Optional: RF antenna pass-through for GPS, WLAN and WWAN

Communication Interface	Wi-Fi 802.11 a/b/g/n/ac Bluetooth (v5.0) ⁱⁱ Dual Micro SIM Dedicated GPS Optional: 4G LTE mobile broadband	
Pre-installed software	Getac File Browser Getac Camera Getac Input Method Getac settings and Google applications (Search, Chrome, Gmail, Maps, YouTube, Play, Drive, Play music, Play movies, Duo and photos)	
Security Feature	Kensington lock Optional: HF RFID/NFC combo reader ⁱ Optional: Smart card reader	
Power	AC adapter (65W, 100-240VAC, 50/60Hz) Li-Ion smart battery(3.84V,typical 4990mAh;min. 4870mAh)x 2 LifeSupport™ battery swappable technology Optional: High capacity battery (3.84V, typical 9980mAh; min. 9470mAh) x 2	
Dimension (W x D x H) & Weigh	275 x 192 x 17.9mm (10.8" x 7.56" x 0.7") 1.04kg (2.29lbs) ^{III}	
Rugged Feature	MIL-STD-810H certified IP66 certified Vibration & 6 feet (1.8m) drop resistant Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D)	
Environmental Specification	Temperature ^{iv} : - Operating: -29°C to 63°C / -20°F to 145°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH, non-condensing	

Accessories

Battery (3.84V, typical 4990mAh; min. 4870mAh) AC adapter (65W, 100-240VAC, 50/60Hz) Capacitive stylus with tether

Optional:

Carry bag High capacity battery (3.84V, typical 9980mAh; min. 9470mAh) Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay) 100W Type-C AC adapter Office dock AC adapter (65W, 100-240VAC) DC-DC vehicle adapter (120W, 22-32VDC) Protection film Hand strap Shoulder strap (2-point) Shoulder strap (2-point; handsfree) Hard handle Keyboard dock Office dock Vehicle Dock

Bumper-toBumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. **Standard** 3 years Bumper-to-Bumper

- I. 13.56MHz HF RFID/NFC combo reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- II. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- III. Weight and dimensions vary from configurations and optional accessories; optional high-capacity batteries add approx. 7.65mm (H), 144g.
- IV. Tested by an independent third-party test lab following MIL-STD-810H.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

04

	Office Dock (Pogo)
Serial Port	-
Microphone	1
Audio Output	1
DC in Jack	1
USB	USB 2.0 x 3
LAN	1
HDMI	1
RF Pass-through	-
Kensington Lock	1

Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom

Tel : +44 (0) 1952 207 222

Sales-Getac-UK@getac.com I www.getac.com/en/ Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

